



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

#### 1 Identification

- · Product Identifier
- · Trade name: Penofin 100 VOC Original Blue Label Formula
- Relevant identified uses of the substance or mixture and uses advised against:
- · *Product Description* Semi-transparent stain for use on wood.
- · Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier:

Performance Coating, Inc.

P.O. Box 1569

360 Lake Mendocino Drive

Ukiah, CA 95482

Phone: (707) 462-3023 Fax: (707) 462-6139

Emergency telephone number: Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887

## 2 Hazard(s) Identification

· Classification of the substance or mixture:



GHS08 Health hazard

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





GHS07 GHS08

· Signal word: Danger

Hazard-determining components of labeling:

Solvent naphtha (petroleum), medium aliph.

Titanium Dioxide
2-butanone oxime





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

#### Trade name: Penofin 100 VOC Original Blue Label Formula

#### · Hazard statements:

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

### Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P330 Rinse mouth.

P331 Do NOT induce vomiting.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Unknown acute toxicity:

58.3 % of the mixture consists of component(s) of unknown toxicity.

## · Classification system:

NFPA ratings (scale 0 - 4)



Health = 1 Fire = 0

Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



· Hazard(s) not otherwise classified (HNOC): None known

## 3 Composition/Information on Ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with non-hazardous additions.

(Contd. on page 3)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

### Trade name: Penofin 100 VOC Original Blue Label Formula

· Dangerous Compone	ents:	
CAS: 64742-88-7	Solvent naphtha (petroleum), medium aliph.	10-25%
	♦ Flam. Liq. 3, H226; ♦ STOT RE 1, H372; Asp. Tox. 1, H304	
CAS: 13463-67-7	Titanium Dioxide	0-10%
	♦ Carc. 2, H351	
CAS: 1330-20-7	Xylene, mixture of isomers	0-10%
RTECS: ZE 2100000	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 100-41-4	Ethylbenzene	<2.5%
RTECS: DA 0700000	♦ Flam. Liq. 2, H225; ♦ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H332	
CAS: 15956-58-8	Manganese carboxylate	<2.5%
	Acute Tox. 1, H300;  Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
CAS: 96-29-7	2-butanone oxime	<2.5%
RTECS: EL9275000	♦ Carc. 2, H351; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H312; Skin Sens. 1 H317; Flam. Liq. 4, H227	,
CAS: 8052-41-3	Stoddard solvent	<2.5%
RTECS: WJ 8925000	♦ Flam. Liq. 3, H226; ♦ Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304	

## 4 First-Aid Measures

- · Description of first aid measures:
- · General information:

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· After eve contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

## 5 Fire-Fighting Measures

- Extinguishing media:
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture: No further relevant information available.

(Contd. on page 4)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

#### Trade name: Penofin 100 VOC Original Blue Label Formula

- · Advice for firefighters:
- Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

## 6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures: Not required.
- Environmental precautions: Do not allow to enter sewers/surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and Storage

- · Handling
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Protect from heat.

Keep protective respiratory device available.

- · Conditions for safe storage, including any incompatibilities:
- Storage
- · Requirements to be met by storerooms and receptacles: Store in the original container.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s): No further relevant information available.

## 8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:

#### 8001-26-1 Linseed oil

TWA Short-term value: 5 mg/m³ Long-term value: 10 mg/m³

(Contd. on page 5)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

### Trade name: Penofin 100 VOC Original Blue Label Formula

1330	-20-7 Xylene, mixture of isomers			
PEL	Long-term value: 435 mg/m³, 100 ppm			
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm			
TLV	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI			
8052	41-3 Stoddard solvent			
PEL	Long-term value: 2900 mg/m³, 500 ppm			
REL	Long-term value: 350 mg/m³ Ceiling limit value: 1800* mg/m³ *15-min			
TLV	Long-term value: 525 mg/m³, 100 ppm			
· Ingre	Ingredients with biological limit values:			
1330	1330-20-7 Xylene, mixture of isomers			
	BEI 1.5 g/g creatinine			
urine end of shift				
	Methylhippuric acids			

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

#### Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

### Trade name: Penofin 100 VOC Original Blue Label Formula

· Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

### 9 Physical and Chemical Properties

<100 gram/liter

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Colored Colored

· Odor: Solvent / Mineral Spirits

Odor threshold: Not determined.pH-value: Not determined.

Change in condition

Melting point/Melting range:<br/>Boiling point/Boiling range:Not determined.<br/>136 °C (277 °F)Flash point:122 °C (252 °F)Flammability (solid, gaseous):Not applicable.Ignition temperature:265 °C (509 °F)

· **Auto igniting:** Product is not self-igniting.

Not determined.

· Danger of explosion: Not determined.

· Explosion limits:

**Lower:** 0.6 Vol % **Upper:** 6.5 Vol %

• Vapor pressure @ 20 °C (68 °F): 6.6 hPa (5 mm Hg)

· Density:

Relative density:Not determined.Vapor density:Not determined.Evaporation rate:Not determined.

· Solubility in / Miscibility with:

Decomposition temperature:

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined.

(Contd. on page 7)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

### Trade name: Penofin 100 VOC Original Blue Label Formula

*Kinematic:* Not determined.

Solvent content:

Organic solvents: 17.2 % VOC content: 17.2 %

**Solids content:** Not Determined

· Other information: No further relevant information available.

## 10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

· LD/LC50 v	values tha	t are relevant for classification:	
64742-88-	64742-88-7 Solvent naphtha (petroleum), medium aliph.		
Oral	LD50	>6500 mg/kg (Rat)	
Dermal	LD50	>3000 mg/kg (rab)	
Inhalative	LC50/4 h	>14 mg/l (Rat)	
13463-67-	7 Titaniun	n Dioxide	
Oral	LD50	>10000 mg/kg (Rat)	
Dermal	LD50	>10000 mg/kg (Rabbit)	
Inhalative	LC50/4 h	>6.82 mg/l (Rat)	
1330-20-7	Xylene, m	nixture of isomers	
Oral	LD50	4300 mg/kg (Rat)	
Dermal	LD50	1700 mg/kg (Rabbit)	
Inhalative	LC50/4 h	5000 mg/l (Rat)	
112-80-1	112-80-1 Oleic acid, pure		
Oral	LD50	74000 mg/kg (Rat)	
100-41-4 E	Ethylbenze	ene	
Oral	LD50	3500 mg/kg (Rat)	
Dermal	LD50	15433 mg/kg (Rabbit)	
64742-48-	64742-48-9 A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65 °C to 230 °C (149 °F to 446 °F).		
Oral	LD50	>5000 mg/kg (Rat)	

(Contd. on page 8)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

### Trade name: Penofin 100 VOC Original Blue Label Formula

Dermal	LD50	>3000 mg/kg (rab)	
96-29-7 2-butanone oxime			
Oral	LD50	3700 mg/kg (Rat)	
Dermal	LD50	200-2000 mg/kg (Rat)	
Inhalative	LC50/4 h	20 mg/l (Rat)	
8052-41-3	-3 Stoddard solvent		
Oral	LD50	>7000 mg/kg (Rat)	
Dermal	LD50	>2000 mg/kg (Rabbit)	

### · Primary irritant effect:

On the skin:

Irritant to skin and mucous membranes.

May cause an allergic skin reaction.

On the eye:

Irritating effect.

Causes serious eye irritation.

## · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Irritant

Carcinogenic

The product can cause inheritable damage.

- · Carcinogenic categories:
- · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

- (a) Although IARC has classified titanium dioxide as possible carcinogenic to human (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is bound to other materials, such as in cosmetics or in paints."
- (b) OSHA does not regulate Titanium Dioxide as a carcinogen. However, under 29 CFR 1910.1200 the SDS must convey the fact that Titanium Dioxide is a potential carcinogen to rats.

13463-67-7	Titanium Dioxide	2B	
1330-20-7	Xylene, mixture of isomers	3	
100-41-4	Ethylbenzene	2B	
· NTP (National Toxicology Program):			
None of the ingredients are listed.			
· OSHA-Ca (0	· OSHA-Ca (Occupational Safety & Health Administration):		
None of the	None of the ingredients are listed.		

## 12 Ecological Information

· Toxicity:

· Aquatic toxicity:	
13463-67-7 Titanium Dioxide	
EC50 >1000 mg/l (Water flea)	

(Contd. on page 9)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

### Trade name: Penofin 100 VOC Original Blue Label Formula

1330-20-7 Xylene, mixture of isomers				
EC50	'2 mg/l (Green algae)			
	75.49 mg/l (Daphnia)			
100-4	1-4 Ethylbenzene			
EC50	4.9 mg/l (Green algae)			
	1.8-2.4 mg/l (Water flea)			

- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes: Not known to be hazardous to water.
- · Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects: No further relevant information available.

## 13 Disposal Considerations

- · Waste treatment methods:
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

## 14 Transport Information

· UN-Number:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name:

· DOT, ADR/ADN, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es):

· DOT, ADR/ADN, ADN, IMDG, IATA

· Class: Non-Regulated Material

· Packing group:

· DOT, ADR/ADN, IMDG, IATA Non-Regulated Material

Environmental hazards: Not applicable.
 Special precautions for user: Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

· Transport/Additional information:

· DOT

· Remarks: Non-Regulated

· UN "Model Regulation": Non-Regulated Material

(Contd. on page 10)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

Trade name: Penofin 100 VOC Original Blue Label Formula

## 15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- · SARA (Superfund Amendments and Reauthorization):

· S	Section 355 (extremely hazardous substances):
N	None of the ingredients are listed.
٠ ج	Section 313 (Specific toxic chemical listings):
1	1330-20-7 Xylene, mixture of isomers
	100-41-4 Ethylbenzene
· 7	TSCA (Toxic Substances Control Act):
Δ	All ingredients are listed or exempt from listing

- · California Proposition 65:
- Chemicals known to cause cancer:

  13463-67-7 | Titanium Dioxide

100-41-4 Ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories:

our onregon	io categorico.			
· EPA (Enviro	onmental Protection Agency):			
1330-20-7	Kylene, mixture of isomers			
100-41-4 E	Ethylbenzene	D		
· TLV (Thres	TLV (Threshold Limit Value established by ACGIH):			
13463-67-7	Titanium Dioxide	A4		
1330-20-7	Xylene, mixture of isomers	A4		
100-41-4	Ethylbenzene	A3		
· NIOSH-Ca (National Institute for Occupational Safety and Health):				
13463-67-7	Titanium Dioxide			

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



· Signal word: Danger





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

### Trade name: Penofin 100 VOC Original Blue Label Formula

#### · Hazard-determining components of labeling:

Solvent naphtha (petroleum), medium aliph.

Titanium Dioxide

2-butanone oxime

#### · Hazard statements:

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

#### · Precautionary statements:

P201	Obtain special instructions be	efore use.
------	--------------------------------	------------

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P330 Rinse mouth.

P331 Do NOT induce vomiting.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Date of preparation / last revision: 03/27/2017 / 17
- · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017 Reviewed on 03/27/2017

## Trade name: Penofin 100 VOC Original Blue Label Formula

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3
Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 1: Acute toxicity – Category 1 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

Muta. 1B: Germ cell mutagenicity - Category 1B

Muta. 2: Germ cell mutagenicity - Category 2

Carc. 1B: Carcinogenicity – Category 1B Carc. 2: Carcinogenicity – Category 2 Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

#### \* Data compared to the previous version altered.

+1-877-204-9106 SDS created by MSDS Authoring Services www.msdsauthoring.com