

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Page 1/12

Identification

- · Product Identifier
- · Trade name: Penofin 100 VOC Pressure Treated Formula
- Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description Semi-transparent stain for use on wood.
- · Details of the Supplier of the Safety Data Sheet:

Manufacturer/Supplier: Performance Coating, Inc.
P.O. Box 1569
360 Lake Mendocino Drive
Ukiah, CA 95482
Phone: (707) 462-3023
Fax: (707) 462-6139
Emergency telephone number: Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887

2 Hazard(s) Identification

· Classification of the substance or mixture:

GHS08 Health hazard

Muta. 2 H341 Suspected of causing genetic defects.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements:
- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

• Hazard pictograms:



· Signal word: Danger

• *Hazard-determining components of labeling:* Solvent naphtha (petroleum), medium aliph.

2-butanone oxime

Hazard statements:

H302 Harmful if swallowed. H317 May cause an allergic skin reaction.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Trade name: Penofin 100 VOC Pressure Treated Formula

- H341 Suspected of causing genetic defects.
- H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

- Precautionary statements:
- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P330 Rinse mouth.
- P331 Do NOT induce vomiting.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- P363 Wash contaminated clothing before reuse.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Unknown acute toxicity:

58.3 % of the mixture consists of component(s) of unknown toxicity.

- Classification system:
- NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)

HEALTH *1	Health = *1
FIRE 0	Fire = 0
REACTIVITY 0	Reactivity = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:

CAS: 64742-88-7	Solvent naphtha (petroleum), medium aliph.	5-20%
	🚸 Flam. Liq. 3, H226; 🚸 STOT RE 1, H372; Asp. Tox. 1, H304	

(Contd. on page 3)

Page 2/12



Page 3/12

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Trade name: Penofin 100 VOC Pressure Treated Formula

CAS: 1330-20-7	Xylene, mixture of isomers	2-12%
RTECS: ZE 2100000	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 100-41-4	Ethylbenzene	<2.5%
RTECS: DA 0700000	 Flam. Liq. 2, H225; Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 	,
CAS: 96-29-7	2-butanone oxime	<2.5%
RTECS: EL9275000	♦ Carc. 2, H351; Eye Dam. 1, H318; Acute Tox. 4, H312; Skin Sens. 1, H317; Flam. Liq. 4, H227	
CAS: 8052-41-3	Stoddard solvent	<2.5%
RTECS: WJ 8925000	Flam. Liq. 3, H226; Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304	
CAS: 64742-48-9	A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65 °C to 230 °C (149 °F to 446 °F).	<2.5%
	🚸 Asp. Tox. 1, H304; Flam. Liq. 4, H227	

4 First-Aid Measures

[.] Description of first aid measures:

• General information:

Immediately remove any clothing soiled by the product.

- In case of irregular breathing or respiratory arrest provide artificial respiration.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

- · After eye contact:
- Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:
- No further relevant information available.

5 Fire-Fighting Measures

- Extinguishing media:
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters:
- Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures: Not required.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Trade name: Penofin 100 VOC Pressure Treated Formula

- Environmental precautions: Do not allow to enter sewers/surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

· Handling

· Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

Prevent formation of aerosols.

- Information about protection against explosions and fires:
- Protect from heat.

Keep protective respiratory device available.

- · Conditions for safe storage, including any incompatibilities:
- · Storage
- · Requirements to be met by storerooms and receptacles: Store in the original container.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed. Protect from heat and direct sunlight.

Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

- Control parameters:
- Components with occupational exposure limits:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

8001-	-26-1 Linseed oil
TWA	Short-term value: 5 mg/m ³ Long-term value: 10 mg/m ³
1330-	-20-7 Xylene, mixture of isomers
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI

(Contd. on page 5)

Page 4/12



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Trade name: Penofin 100 VOC Pressure Treated Formula

8052	-41-3 Stoddard solvent
PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m³ Ceiling limit value: 1800* mg/m³ *15-min
TLV	Long-term value: 525 mg/m ³ , 100 ppm
· Ingre	dients with biological limit values:
1330-	-20-7 Xylene, mixture of isomers
ц е Г	1.5 g/g creatinine urine end of shift Methylhippuric acids
	tional information: The lists that were valid during the creation of this SDS were used as basis.
Perse Gene The u Keep Imme Wash Store Avoid	asure controls: onal protective equipment: aral protective and hygienic measures: usual precautionary measures for handling chemicals should be followed. away from foodstuffs, beverages and feed. adiately remove all soiled and contaminated clothing and wash before reuse. a hands before breaks and at the end of work. protective clothing separately. I contact with the eyes and skin. thing equipment: Not required. action of hands:
1112 ILL	Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

• Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection:



Tightly sealed goggles

(Contd. on page 6)



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Trade name: Penofin 100 VOC Pressure Treated Formula

9 Physical and Chemical Properties		
<100 gram/liter		
 Information on basic physical and ch General Information Appearance: Form: Color: Odor: Odor threshold: 	Liquid Colored Solvent / Mineral Spirits Not determined.	
· pH-value:	Not determined.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not determined. 136 °C (277 °F)	
· Flash point:	122 °C (252 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	265 °C (509 °F)	
• Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not self-igniting.	
• Danger of explosion:	Not determined.	
 Explosion limits: Lower: Upper: 	0.6 Vol % 6.5 Vol %	
· Vapor pressure @ 20 °C (68 °F):	6.6 hPa (5 mm Hg)	
 Density: Relative density: Vapor density: Evaporation rate: 	Not determined. Not determined. Not determined.	
 Solubility in / Miscibility with: Water: 	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water)): Not determined.	
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.	
 Solvent content: Organic solvents: VOC content: 	17.2 % 17.2 %	
Solids content: • Other information:	Not Determined No further relevant information available.	

(Contd. on page 7)

Page 6/12



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Trade name: Penofin 100 VOC Pressure Treated Formula

10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

		at are relevant for classification:
		naphtha (petroleum), medium aliph.
Oral	LD50	>6500 mg/kg (Rat)
	LD50	>3000 mg/kg (rab)
Inhalative	LC50/4 h	>14 mg/l (Rat)
13463-67-7	7 Titaniun	n Dioxide
Oral	LD50	>10000 mg/kg (Rat)
Dermal	LD50	>10000 mg/kg (Rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (Rat)
1330-20-7	Xylene, n	nixture of isomers
Oral	LD50	4300 mg/kg (Rat)
Dermal	LD50	1700 mg/kg (Rabbit)
Inhalative	LC50/4 h	5000 mg/l (Rat)
112-80-1 C	Dleic acid,	, pure
Oral	LD50	74000 mg/kg (Rat)
100-41-4 E	Ethylbenzo	ene
Oral	LD50	3500 mg/kg (Rat)
Dermal	LD50	15433 mg/kg (Rabbit)
64742-48-	hydrogo number	lex combination of hydrocarbons obtained by treating a petroleum fraction with en in the presence of a catalyst. It consists of hydrocarbons having carbon rs predominantly in the range of C6 through C13 and boiling in the range of mately 65 °C to 230 °C (149 °F to 446 °F).
Oral	LD50	>5000 mg/kg (Rat)
Dermal	LD50	>3000 mg/kg (rab)
96-29-7 2-	butanone	oxime
	LD50	3700 mg/kg (Rat)
Oral	LDOO	
	LD50	200-2000 mg/kg (Rat)



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Page 8/12

Trade name: Penofin 100 VOC Pressure Treated Formula

8052-4	1-3 Stoddar	d solvent	
Oral	LD50	>7000 mg/kg (Rat)	
Derma	I LD50	>2000 mg/kg (Rabbit)	
 On the Irritant May ca On the Irritatin Cause Additi The p prepar Toxic Irritant Carcin 	to skin and m ause an allerg e eye: g effect. s serious eye onal toxicolo roduct show ations:	nucous membranes. gic skin reaction.	ds for
· <i>IARC</i> None of (a) Alt conclu titaniur (b) OS must of	of the ingredie hough IARC des: "No sigr n dioxide is b HA does not onvey the fac	A Agency for Research on Cancer): ents are listed. has classified titanium dioxide as possible carcinogenic to human (2B), their sur inficant exposure to titanium dioxide is thought to occur during the use of products yound to other materials, such as in cosmetics or in paints." regulate Titanium Dioxide as a carcinogen. However, under 29 CFR 1910.1200 th ct that Titanium Dioxide is a potential carcinogen to rats.	which e SDS
	-67-7 Titaniu		2B
	-	, mixture of isomers	3
100-	-41-4 Ethylbe	enzene	2B
•		icology Program):	
None	of the ingredie	ents are listed.	
· OSHA	-Ca (Occupa	ntional Safety & Health Administration):	
None	of the ingredie	ents are listed.	
12 Ecolo	ogical Info	rmation	
· Toxici	ty:		
· Aquat	ic toxicity:		
13463	-67-7 Titaniu	m Dioxide	
	>1000 mg/l (•	
	-	mixture of isomers	
	72 mg/l (Gree		
	75.49 mg/l (E		
	-4 Ethylbenz		
EC50	4.9 mg/l (Gre	een algae)	

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Trade name: Penofin 100 VOC Pressure Treated Formula

1.8-2.4 mg/l (Water flea)

· Persistence and degradability: No further relevant information available.

- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- *Mobility in soil:* No further relevant information available.
- Additional ecological information:
- · General notes: Not known to be hazardous to water.
- Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods:
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

14 Transport Information	
· UN-Number: · DOT, ADR/ADN, ADN, IMDG, IATA · UN proper shipping name:	Non-Regulated Material
· DOT, ADR/ADN, ADN, IMDG, IATA · Transport hazard class(es):	Non-Regulated Material
DOT, ADR/ADN, ADN, IMDG, IATA	Non-Regulated Material
 Packing group: DOT, ADR/ADN, IMDG, IATA Environmental hazards: 	Non-Regulated Material Not applicable.
Special precautions for user: Transport in bulk according to Annex II	Not applicable.
MARPOL73/78 and the IBC Code:	Not applicable.
· Transport/Additional information:	
· DOT · Remarks: · UN "Model Regulation":	Non-Regulated Non-Regulated Material
15 Regulatory Information	

• Safety, health and environmental regulations/legislation specific for the substance or mixture: • SARA (Superfund Amendments and Reauthorization):

• Section 355 (extremely hazardous substances):

None of the ingredients are listed.

*

(Contd. on page 10)

Page 9/12



Page 10/12

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Trade name: Penofin 100 VOC Pressure Treated Formula

Section 313 (Specific toxic chemical listings):	
1330-20-7 Xylene, mixture of isomers	
100-41-4 Ethylbenzene	
• TSCA (Toxic Substances Control Act):	
All ingredients are listed or exempt from listing.	
· California Proposition 65:	
· Chemicals known to cause cancer:	
13463-67-7 Titanium Dioxide	
100-41-4 Ethylbenzene	
• Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
· Carcinogenic categories:	
· EPA (Environmental Protection Agency):	
1330-20-7 Xylene, mixture of isomers	
100-41-4 Ethylbenzene	D
• TLV (Threshold Limit Value established by ACGIH):	
13463-67-7 Titanium Dioxide	A4
1330-20-7 Xylene, mixture of isomers	A4
100-41-4 Ethylbenzene	A3
NIOSH-Ca (National Institute for Occupational Safety and Health):	
13463-67-7 Titanium Dioxide	
· GHS label elements	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms:*



· Signal word: Danger

- Hazard-determining components of labeling: Solvent naphtha (petroleum), medium aliph.
 2-butanone oxime
- · Hazard statements:
- H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Page 11/12

Trade name: Penofin 100 VOC Pressure Treated Formula

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P308+P313 IF exposed or concerned: Get medical advice/attention.

- P314 Get medical advice/attention if you feel unwell.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P330 Rinse mouth.
- P331 Do NOT induce vomiting.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 03/27/2017 / 21

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

- DOT: US Department of Transportation
- IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative

IMDG: International Maritime Code for Dangerous Goods

NIOSH: National Institute for Occupational Safety and Health



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/27/2017

Reviewed on 03/27/2017

Trade name: Penofin 100 VOC Pressure Treated Formula

OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BE: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 4 Acute Tox. 4: Acute toxicity – Category 4 Skin Irit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Muta. 1B: Germ cell mutagenicity – Category 1B Muta. 2: Germ cell mutagenicity – Category 2 Carc. 1B: Carcinogenicity – Category 2 Carc. 2: Carcinogenicity – Category 2 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 * **Data compared to the previous version altered.** SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106 Page 12/12