


8 9 10 11 12
 (00) 1 2 3 4 5 6 7
 8 9 10 11 12
 (00) 1 2 3 4 5 6 7
 8 9 10 11 12
 (00)

ASPEN

PENOFIN®
LOG ON



**FOR: LOG HOMES -
 TIMBER FRAME HOMES - FURNITURE
 99% U.V. PROTECTION SUSTAINABLY
 HARVESTED BRAZILIAN ROSEWOOD OIL**



**ONCE OPENED, THIS IS NOT AN AIRTIGHT
 CONTAINER. USE THE ENTIRE CONTENTS
 OF THIS PAIL UPON OPENING.**



LOG ON® LOG AND TIMBERFRAME FINISH

FOR EXTERIOR USE ONLY

LOG ON is a quality oil wood finish for log and timber frame protection and enhancement. LOG ON is a deeply penetrating finish that uses sustainably harvested Brazilian Rosewood Oil. LOG ON is a transparent wood finish rated with a 99% ultraviolet rating and has added mildew protection. Log and timber frame buildings will look beautiful and last longer with LOG ON. Penofin complies with all national and local air quality regulations. V.O.C. content less than 550 grams per liter.

NOTE TO USER:

Please read label instructions carefully. This product will vary in appearance depending on the texture and condition of the wood. To ensure desired appearance always apply to a small test area and allow to dry completely before continuing.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you begin, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.

APPLICATION

SURFACE PREPARATION:

- Wood surface must be free of all contamination such as dirt, mildew and loose wood fibers.
- Surface must be in sound condition and absolutely dry. New wood, once dry, should not be allowed to weather.
- Wash new borate-treated logs with a detergent solution before finishing with Penofin.
- Recondition previously stained or weathered wood surfaces; remove all prior finish with a stiff nonmetallic bristle brush, pressure-washing unit, or paint stripper.

Extractive bleeding: Follow directions on product label. Extractive bleeding does not represent a coating failure; it is a natural event caused by wood tannins.

FINISHING: Stir thoroughly before and occasionally while applying. A natural bristle brush or sprayer achieves the best results. When spraying, apply only as much product as wood will absorb. Do not over saturate. Proper application will result in a non glossy, flat-matte finish.

TO APPLY: On **softwood**, start with one liberal coat. Following 20 minutes absorption time, wipe entire surface with a nap-free cloth. If wood is rough sawn, back brush with a dry brush to remove excess. Wait a minimum three-hour drying time and apply a second coat. Wipe entire surface within 20-30 minutes of follow-up application. On new **hardwood**, only one coat is recommended. If project requires more than one container, blend all containers together. This product will weather naturally. Apply a maintenance coat every 3-5 years depending on exposure.

RESTRICTIONS: Do not apply when wood is hot to the touch, or when air surface temperature is below 45° F. Do not apply over wet or damp surfaces or when rain is imminent. Warranty is void if blended or thinned, or tinted with other products.

COVERAGE: Coverage will vary from 175-300 square feet depending on surface: if logs are rustic or milled, moisture content, and method of application.

CLEAN UP: Paint thinner or mineral spirits.

LIMITED WARRANTY: Penofin exterior finishes are warranted to perform when applied to wood surfaces according to label instructions. If Penofin is shown to be defective, Performance Coatings Inc. will replace the product. Warranty is void if wood was previously finished or pretreated. Performance Coatings Inc.'s liability under any warranty whether expressed or implied is limited solely to replacement of product and does not include labor or other consequential damages.

**MANUFACTURED BY PERFORMANCE COATINGS INC.
 360 LAKE MENDOCINO DRIVE, P.O. BOX 1569 • UKIAH, CA 95482
 1-800-PENOFIN • Se Habla Español • www.penofin.com**

CAUTION Contains: Petroleum Distillate

Keep away from flame. Do not smoke during application. For exterior application only. Vapor harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. Causes eye, skin, nose, and throat irritation. Intentional misuse by deliberately concentrating or inhaling the contents may be harmful or fatal.

Use only with proper ventilation. Avoid breathing vapors or spray mist during the application and drying. If you experience eye watering, headache, or dizziness leave the area or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent). Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Limited shelf life after opening.

DANGER: Rags, steel wool or waste soaked with Penofin Exterior Wood Finish may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container away from building and other combustible materials. Dispose of in accordance with local regulations.

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

First aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If breathing difficulties persist, seek medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water.

KEEP OUT OF THE REACH OF CHILDREN

¡PRECAUSION! CONTIENE: VAPOR DE PETRÓLEO

Inflamable. Asegurarse en lugar ventilado. Aplicable para exterior solamente.

Vapor peligroso. Talvez afecte el cerebro o el sistema nervioso causando mareos, dolores de cabeza. Causa sus ojos, piel, nariz, y garganta irritada. Si lo usa mal o al propósito to hule este producto puede perguunicarlo o fatal.

Solamente usuelo en lugar bien ventilado y adecuada. Si siente dolores de cabeza, mareos y ojos irritados, deje la área y pongas protección respiratoria (NIOSH/MSHA TC 23C o algo igual). Sierra el vote después de usaria. Lavese las manos después de agarrar oste producto.

ESTE PRODUCTO PUESE ENSEDERSE INSTANTNIAMENTE. Ropa mojada de aceite, brochas, trapos, etc. Pongamos en agua y sierra completamente el vote manténgalo fuera de otros productos inflamables.

¡ADVERTENCIA! Este producto contiene productos químicos conocidos al estado de California para causar cáncer, y defectos de nacimiento u otro daño reproductivo.

Primera atención medica: si a sido in gestionado, no intrudusa vomito. Llame a un doctor inmediatamente. Si se siente con dificultad respiratoria, deja el lugar y oblenaga aire fresco. Si continúe con la misma experiencia, obtenga atención medica inmediatamente. Si tiene contacto con sus ojos, lavelos con mucha agua por los menos por 15 minutos y obtenga atención medica; en su piel lavese completamente con agua y jabón.

MANTENGALO FUERA DEL ALCANCE DE LOS NIÑOS

"Penofin The World's Finest Wood Finish®"

DANGER!
 HARMFUL OR FATAL IF SWALLOWED.
 VAPOR HARMFUL. COMBUSTIBLE LIQUID AND VAPOR.
 See other Cautions on Back Panel.

**NET 128 fl. oz.
 (ONE GALLON)
 3.785 liters**

PC-2051-1(550 VOC) PMS3298