

# Material Safety Data Sheet

DATE OF PRINTING: 01/24/05

HMIS: H1F0R0

---

## Section 1

---

MANUFACTURER: PERFORMANCE COATINGS INC.  
360 Lake Mendocino Drive  
Ukiah, California 95482

TELEPHONE: (707) 462-3023

PRODUCT CLASS: Semitransparent Wood Stain

CODE IDENTIFICATION: Aquafin®

TRADE NAME: Waterborne Latex – (various colors) 100 V.O.C. formula

EMERGENCY TELEPHONE NUMBERS: FOR CHEMICAL EMERGENCY. Spill, leak, fire, exposure or accident. Call CHEMTREC - Day or Night - 1-800-424-9300. Outside the United States call 202-483-7616.

EMERGENCY POISONING TREATMENT INFORMATION: Call collect 24 hours a day – 1-800-947-2331.

DOT SHIPPING NAME: Paint Related Material, UN1263

---

## Section 2 – Composition/Information On Ingredients

---

### PERCENT BY WEIGHT

---

142 Solvent	CAS NUMBER: MIXTURE	2.70%
Dipropylene Glycol Methyl Ether	CAS NO:34590-94-8	3.22%
Triethylamine	CAS NUMBER: 121-44-8	0.61%
Non –hazardous ingredients		86.21%

---

### Section 3 - Physical Data

---

PH:	8.5 TO 9.5
WEIGHT PER LB.S/GALLON	8.45
EVAPORATION RATE: Slower than ether.	WEIGHT PER LB.S/ GALLON: 8.45
VAPOR DENSITY:	GREATER THAN 1(AIR=1) . . . :
VOCS:	<100 GRAMS/LITER
FLASH POINT:	NO DATA
APPEARANCE AND ODOR:	COLORLESS LIQUID SLIGHT

---

### Section 4 - Hazard Data

Irritant

---

FLASH POINT: No Data

UNUSUAL FIRE OR EXPLOSION HAZARDS: Keep away from heat, sparks, or open flame.

SPECIAL FIRE FIGHTING PROCEDURES: Positive pressure self-contained breathing apparatus (SCBA) should be worn to avoid inhalation of concentrated vapors. Chemical protective clothing is recommended if there may be repeated or prolonged exposure to the liquid or concentrated vapors.

---

### Section 5 – First Aid Measures

---

THRESHOLD LIMIT VALUE: See Section II

PRIMARY ROUTE(S) OF ENTRY: Dermal, ingestion, inhalation.

EFFECTS OF OVEREXPOSURE: Acute -Eye or skin contact may cause irritation. Can be irritating to the respiratory tract if inhaled as a mist or concentrated vapor. Inhalation of the vapors, or ingestion of the liquid, can cause systemic toxicity including dizziness, confusion, drowsiness, un-coordination, staggering gait, nausea, headache. Aspiration may also lead to chemical pneumonia  
Chronic -Reports have associated repeated and prolonged overexposure to solvents with permanent brain damage and nervous system damage.

---

## Section 5 – First Aid Measures (Cont'd)

---

### EMERGENCY FIRST AID PROCEDURES:

**INHALATION:** Remove to fresh air.

**SKIN:** Promptly remove contaminated clothing and wash with soap and water, Get medical attention if irritation develops or persists.

**EYES:** Irritant, immediately with water or saline for at least 10-15 minutes.

**INGESTION:** Do not induce vomiting. Call a physician immediately and/or transport to emergency facility immediately.

---

---

## Section 6 – Accidental Release Measures

---

PERSONAL PRECAUTIONS: see section 7

SPILLS: Absorb spill with inert material such as dry sand or sawdust, then place in a chemical waste container. Provide ventilation. Clean up spills immediately. Avoid any runoff into storm sewers, ditches and waterways.

---

---

## Section 7- Special Protection Information

---

SKIN PROTECTION: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material. Selection of specific items such as gloves, boots, apron, or fully body suit will depend on operation.

EYE PROTECTION: Use safety glasses. Where contact with liquid is likely, chemical goggles are recommended.

OTHER PROTECTIVE EQUIPMENT: It is suggested that a source of clean water be available in work area for flushing eyes and skin.

---

## Section 8 - Special Precautions

---

PRECAUTIONS TO BE TAKEN IN HANDLING OR STORING: Do not store below 32 °\_F. above 125°\_F.

OTHER PRECAUTIONS: Do not take internally. Do not use in areas of inadequate ventilation.

---

## Section 9 - Sara 313 Information

---

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>% BY WEIGHT</u>
Dipropylene glycol methyl ether	34590-94-8	3.22%
Triethylamine	121-44-8	0.61%
Solvent 142	Mixture	2.70%

---

PREPARED BY: Regulatory Director, Performance Coatings Inc., Ukiah, California 95482

REFERENCE DATE: January 24, 2005

### **WARNING**

Detectable amounts of some chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be found in various petroleum products and chemical products you purchase from Performance Coatings Inc., in their vapors, or may result from their use. Use care when handling or using all chemical and petroleum products.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.