

Material Safety Data Sheet

DATE OF PRINTING: 01/01/2010

HMIS: H1F1R0

Section 1

MANUFACTURER: PERFORMANCE COATINGS INC.
360 Lake Mendocino Drive
Ukiah, California 95482

TELEPHONE: (707) 462-3023

PRODUCT CLASS: Semitransparent Stain

CODE IDENTIFICATION: Penofin® - Verde

TRADE NAME: Penofin Exterior and Interior oil – (various colors) 0 V.O.C. formula

EMERGENCY TELEPHONE NUMBERS: FOR CHEMICAL EMERGENCY. Spill, leak, fire, exposure or accident. Call CHEMTREC - Day or Night - 1-800-424-9300. Outside the United States call 202-483-7616.

EMERGENCY POISONING TREATMENT INFORMATION: Call collect 24 hours a day – 1-800-222-1222

DOT SHIPPING NAME: Paint Related Material

Section 2 – Composition/Information On Ingredients

PERCENT
BY WEIGHT

Non-hazardous ingredients	100%
Vegetable oil mist	
15 mg/m (total particulate)	
5 mg/m (respirable particulate)	

Section 3 - Physical Data

BOILING RANGE: >250°C VAPOR DENSITY (air=1): 1.0

EVAPORATION RATE(n-BU AC=1): NA WEIGHT PER GALLON: 7.8

VAPOR PRESSURE: 0.05 mm VISCOSITY: 184 CTS

MELTING POINT: NA SPECIFIC GRAVITY: 0.944

SOLUBILITY IN WATER: Partially Dispersible in water

APPEARANCE AND ODOR: Amber Liquid Mild Vegetable Oil Odor

Section 4 - Fire and Explosion Hazard Data

OSHA CATEGORY: Combustible Class IIIA

FLASH POINT: 200°F Cleveland Open Cup LEL%: NA UEL%: NA

To avoid spontaneous combustion, soak oily cloths, brushes, rollers, etc. in water after use or place in a closed metal container away from building and other combustible materials. Dispose of in accordance with local regulations.

EXTINGUISHING MEDIA: Foam, CO2, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: The use of self-contained breathing apparatus is recommended for fire fighters. Do not use heavy stream of water, fatty material will float.

Section 5 - Health Hazard Data

THRESHOLD LIMIT VALUE: See Section II

Section 5 - Health Hazard Data (Cont'd)

EMERGENCY FIRST AID PROCEDURES:

INHALATION: If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention.

SKIN: Promptly remove contaminated clothing and wash with soap and water.

EYES: Irrigate immediately with water or saline for at least 10-15 minutes.

INGESTION: No hazards anticipated from ingestion due to incidental industrial exposure.

Section 6 - Reactivity Data

STABILITY: Stable

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield carbon dioxide and /or carbon monoxide

HAZARDOUS POLYMERIZATION: Will not occur.

Section 7 - Spill or Leak Procedure

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SMALL LEAKS: Mop up, wipe up, or soak up immediately remove to out-of-doors.

LARGE SPILLS: Evacuate area. Contain liquid; transfer to closed metal containers. Keep out of water supplies.

DISPOSAL METHOD: When disposing of the unused contents, the preferred options are to send to licensed reclaimer, or to permitted incinerators. Any disposal practice must be in compliance with federal, state and local regulations. Do not dump into sewers, on the ground, or into any body of water.

Section 8 - Special Protection Information

RESPIRATORY PROTECTION: Use a supplied air respirator when airborne exposure limits are exceeded.

VENTILATION: Mechanical ventilation

Section 8 - Special Protection Information (cont'd)

SKIN PROTECTION: For brief contact, no precautions other than clean body-covering clothing should be needed.

EYE PROTECTION: Use safety glasses. Where contact with liquid is likely, chemical goggles are recommended.

OTHER PROTECTIVE EQUIPMENT: It is suggested that a source of clean water be available in work area for flushing eyes and skin.

Section 9 - Special Precautions

PRECAUTIONS TO BE TAKEN IN HANDLING OR STORING: To maintain product quality, do not store in heat or direct sunlight.

OTHER PRECAUTIONS: Do not take internally.

Section 10 - Sara 313 Information

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>% BY WEIGHT</u>
NA		

PREPARED BY: Regulatory Director, Performance Coatings Inc., Ukiah, California 95482

REFERENCE DATE: July 2008

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.