

8 8 1 0 1 1 2 7 (94) 1 2 3 4 5 6 7 (95) 8 9 1 0 1 1 2 (96) 1 2 3 4 5 6 7 (98) 8 9 1 0 1 1 2 (99)

UN 1263

PRECAUSION

Contiene: Vapor de Petróleo

Inflamable. Asegurase en lugar ventilado. Aplicable para exterior solamente.

Vapor peligroso. Tal vez afecte el cerebro o el sistema nervioso causando mareos, dolores de cabeza. Causa sus ojos, piel, nariz, y garganta irritada. Si lo usa mal o al propósito to hule este producto puede pergunicarlo o fatal.

Solamente usuelo en lugar bien ventilado y adecuada. Si siente dolores de cabeza, mareos y ojos irritados, deje la área y pongas protección respiratoria (NIOSH/MSHA TC 23C o algo igual). Sierre el vote después de usaria. Lavese las manos después de agarrar oste producto.

ESTE PRODUCTO PUESE ENSEDERSE INSTANTNIAMENTE. Ropa mojada de aceite, brochas, trapos, etc. Pongamos en agua y sierre completamente el vote manténgalo fuera de otros productos inflamables.

AVISO este producto contiene chemicals, conocidos de causar el cáncer y defectos de nacimiento y otras coaas mal.

Primera atención medica: si a sido in gestionado, no intrudusa vomito. Llame a un doctor inmediatamente. Si se siente con dificultad respiratoria, deja el lugar y oblenaga aire fresco. Si continúe con la misma experiencia, obtenga atención medica inmediatamente. Si tiene contacto con sus ojos, lavelos con mucha agua por los menos por 15 minutos y obtenga atencion medica; en su piel lavese completamente con agua y jabón.

MANTENGALO FUERA DEL ALCANCE DE LOS NINOS

TRANSPARENT CEDAR **ULTRA PREMIUM**

PENOFIN® PENETRATING OIL FINISH

99% U.V. PROTECTION
BRAZILIAN ROSEWOOD OIL

FOR:
DECKS - SIDING - FENCES
LOG HOMES - FURNITURE

NET 128 fl. oz.
(ONE GALLON)
3.785 liters



EXTERIOR

Use Penofin® exterior wood finishing products on your wood projects to protect against fading and discoloration.

PENOFIN transparent exterior finishes were formulated to safeguard the natural beauty of wood and to prevent discoloration from the sun's ultraviolet rays. Penofin resists stains and retards nail bleed. Penofin complies with all national and local air quality regulations. V.O.C. Less than 550 grams per liter.

APPLICATION: SHAKE WELL AND STIR THOROUGHLY. DO NOT THIN OR BLEND WITH OTHER PRODUCTS. DO NOT APPLY WHEN WOOD IS HOT TO THE TOUCH! Two coats are required for optimum performance and warranty. Apply with brush or sprayer to a clean, dry, unfinished, seasoned or kiln dried wood of any wood species. Do not prepare surface with steel wool. Apply one liberal coat; wait 20 minutes, wipe entire surface. Following a minimum three-hour drying time, apply a light second coat; wipe surface with a nap-free cloth within 20 minutes or excess oil will congeal on surface and result in a tacky finish. Do not apply wet on wet. Surface ready to use twelve hours after final coat. NOTE: DO NOT OVER APPLY. Color may vary according to wood species. Apply a small amount to a hidden area before proceeding..

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD, or log on to www.epa.gov/lead.

COVERAGE: Coverage will vary from 175-300 square feet per gallon depending on the surface texture, moisture content, and method of application.

CLEAN UP: Paint thinner or mineral spirits.

CAUTION Contains: Petroleum Distillate

Keep away from flame. Do not smoke during application. Assure cross ventilation. Avoid vapor build-up. For exterior application only. Vapor harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. Causes eye, skin, nose, and throat irritation. Intentional misuse by deliberately concentrating or inhaling the contents may be harmful or fatal.

Use only with adequate ventilation. Avoid breathing vapors or spray mist during application and drying. If you experience eye watering, headaches, or dizziness, leave the area or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent). Close container after each use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

DANGER: Rags, steel wool or waste soaked with Penofin Exterior Wood Finish may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container away from building and other combustible materials. Dispose of in accordance with local regulations.

WARNING This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

First aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty in breathing, leave area to obtain fresh air. If breathing difficulty continues, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

KEEP OUT OF THE REACH OF CHILDREN

LIMITED WARRANTY: Penofin exterior finishes are warranted to perform when applied to wood surfaces according to label instructions. If Penofin is shown to be defective, Performance Coatings Inc. will replace the product. Warranty is void if wood was previously finished or pretreated. Performance Coatings Inc.'s liability under any warranty whether expressed or implied is limited solely to replacement of product and does not include labor or other consequential damages.

MANUFACTURED BY PERFORMANCE COATINGS INC.
360 LAKE MENDOCINO DRIVE, P.O. BOX 1569 • UKIAH, CA 95482
1-800-PENOFIN • Se Habla Español • www.penofin.com

Penofin The World's Finest Wood Finish®

DANGER!

HARMFUL OR FATAL IF SWALLOWED.
VAPOR HARMFUL. COMBUSTIBLE LIQUID AND VAPOR.
See other Cautions on Back Panel.