



PENOFIN RENEWALL

For Decks & Concrete

PRODUCT DATA SHEET

PENOFIN RENEWALL:

Brings old, worn wood, and concrete back to life. The thick elastomeric formula will fill cracks up to 1/4" and correct unsightly splinters creating an attractive non-slip, non-skid, and dirt resistant surface. Penofin RenewAll is for horizontal surface and will add years to the life of any deck, patio, or porch.

PERFORMANCE FEATURES

- ◆ Barefoot Friendly Surface
- ◆ Low Odor
- ◆ Low VOC
- ◆ Extends the life of wood & masonry surfaces.

RENEWALL APPLICATIONS

- ◆ Decks
- ◆ Patios
- ◆ Sidewalks
- ◆ Masonry

TECHNICAL DATA:

Installation Temperature: 50°F to 80°F. Do not apply if temperature may fall below 50°F within 48 hours.

Dry to the Touch: 1st coat in 4-6 hours, then apply a second coat.

Serviceable: 24 hours after 2nd coat.

Full Cure: 72 hours

Coverage: Approximately 75sq. ft. per gallon. (Requires 2 coats)

VOC: 50 g/l

Resin Type: Elastomeric/Acrylic Latex blend.

Density: 10.99 (lbs/gallon)

Viscosity Krebs: 140-145KU

Solids (% by weight): 65%

Solids (% by volume): 53%

PH: 8.5-9.5

Gloss @ 60°: <4°

Sheen: Flat

Tint Base: Deep

Pre-Tined Colors: Adobe, Pewter, Sea Ranch, Seal, Suede, Terra Cotta

SURFACE PREPARATION:

Remove any loose splinters or fibers, and replace rotting or severely damaged boards.

Prepare the surface with the Pro-Tech Cleaners. Fill in cracks

cracks larger than 1/4" with exterior wood filler. New concrete should cure 30 days before applying the stain. Then treat with Penofin **Pro-Tech Brightener #3**. **Not recommended for driveways or garage floors.**

APPLICATION:

Shake and stir thoroughly before and during use. Blend multiple containers together to ensure uniformity of color. Product can be applied with a brush or roller. Fill cracks and apply to rough areas first, then apply a thick even coat lengthwise along the boards. Allow to dry 4-6 hours, and then apply a second coat. Do not apply over wet or damp surfaces or when rain is imminent. Do not intermix with any other products or thin. Protect containers from freezing. For exterior use only.

May cause eye and skin irritation. Use only with adequate ventilation. Avoid breathing vapors, spray, mist, or sanding dust. If you experience eye watering, headache, or dizziness, wear an appropriate properly fitted respirator (Noish approved) during and after application. Wash thoroughly after handling. Close container after each use. DO NOT TAKE INTERNALLY.

WARNING: This product contains a chemical known to the State of California to cause cancer.

CLEAN UP:

Clean brushes and equipment with soap and water. Dispose of empty cans or unused portion in accordance with local, state and federal regulations.

Please visit our website www.penofin.com for more application & wood care tips, or call our live customer service line at: 1-800-PENOFIN Monday thru Friday 7am to 4pm Pacific Standard Time, or email us at mail@penofin.com.

