

PENOFIN SOLID COLOR ACRYLIC STAIN

For Decks, Siding, & Fences

PRODUCT DATA SHEET

PENOFIN SOLID COLOR ACRYLIC STAIN:

An exceptionally durable stain for use on decking, siding, fencing, composite bords, outdoor furniture, steps, railings, concrete patios, and walkways. The finish is water repellent and fade resistant. Solid color stains provide excellent adhesion to new, previously stained or painted surfaces, which are in clean, sound condition.

PERFORMANCE FEATURES

- ♦ Decks
- ♦ Siding
- ♦ Fencing
- ♦ Composite Wood

SOLID ACRYLIC APPLICATIONS

- ♦ Concrete Sidewalks
- ♦ Patios
- ♦ Walkways

TECHNICAL DATA:

Installation Temperature: 50°F to 80°F.

Dry to the Touch: 4-6 hours then apply another coat.

Serviceable: 24 hours **Full Cure:** 72 hours

Coverage: Approximately 450sq. ft. on smooth surfaces & 200-

300sq. ft. on rough surfaces.

VOC: <100 g/l

Resin Type: 100% Acrylic Latex. Density: 9.06-10.62 (lbs/gallon) Viscosity Krebs: 95-100KU Solids (% by weight): 39-52% Solids (% by volume): 33-39%

PH: 8.5-9.5

Gloss @ 60°: <8-12 degrees

Sheen: Flat

Tint Base: Neutral, Medium & White

SURFACE PREPARATION:

In order to be effective a stain must be able to adhere to the surface. Surfaces must be sound, and absolutely dry. Be sure the surface is free of all dirt, mildew stains, loose wood fibers, and other foreign matter. Old loose surface coatings should be scraped off and edges sanded smooth for proper adhesion. Prior to staining, the entire area should be properly cleaned with Penofin **Pro-Tech Cleaner #2**.

APPLICATION:

Apply with nylon or polyester brush, stain pads or professional spray equipment. When spraying always back-brush immediately. Do not over apply. Shake and stir thoroughly before and during use. If the project requires more than 1 container, blend all containers together to ensure uniformity. Apply to small sections at a time (1-3 boards); to avoid lap marks. Requires 2-coat application.

CLEAN UP:

Clean brushes and equipment with soap and water. Dispose of empty cans or unused portion in accordance with local, state, and federal regulations.

CAUTION! KEEP OUT OF THE REACH OF CHILDREN. My cause eye and skin irritation. Use only with adequate ventilation. Avoid breathing vapors, spray mist, or standing dust. If you experience eye watering, headache, or dizziness, wear an appropriate properly fitted respirator (Niosh approved) during and after application. Wash thoroughly after handling. Close container after each use. DO NOT TAKE INTERNALLY.

WARNING: This product contains a chemical known to the State of California to cause cancer.

Please visit our website www.penofin.com for more application & wood care tips, or call our live customer service line at: 1-800-PENOFIN Monday thru Friday 7am to 4pm Pacific Standard Time, or email us at mail@penofin.com.

