



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

### 1 Identification

- **Product Identifier**
- **Trade name: Penofin 550 VOC Redwood All heart**
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description** Semi-transparent stain for use on wood.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**  
Performance Coating, Inc.  
P.O. Box 1569  
360 Lake Mendocino Drive  
Ukiah, CA 95482  
Phone: (707) 462-3023  
Fax: (707) 462-6139
- **Emergency telephone number:** Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887

### \* 2 Hazard(s) Identification

- **Classification of the substance or mixture:**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.  
Skin Irrit. 2 H315 Causes skin irritation.  
Skin Sens. 1B H317 May cause an allergic skin reaction.  
Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements:**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS02 GHS07

- **Signal word:** Warning
- **Hazard-determining components of labeling:**  
Xylene, mixture of isomers  
Ethylbenzene  
3-Iodo-2-propynylbutylcarbamate  
2-butanone oxime

(Contd. on page 2)



### Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

**Trade name: Penofin 550 VOC Redwood All heart**

**Hazard statements:**

- H226 Flammable liquid and vapor.
- H332 Harmful if inhaled.
- H315+H320 Causes skin and eye irritation.
- H317 May cause an allergic skin reaction.

**Precautionary statements:**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P363 Wash contaminated clothing before reuse.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Danger Spontaneous Combustion:** Rags, steel wool or waste soaked with Penofin exterior wood finish may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container away from buildings and other combustible materials.

**Unknown acute toxicity:**

16.2 % of the mixture consists of component(s) of unknown toxicity.

**Classification system:**

**NFPA ratings (scale 0 - 4)**

**HMIS-ratings (scale 0 - 4)**

|            |   |                |
|------------|---|----------------|
| HEALTH     | 1 | Health = *1    |
| FIRE       | 2 | Fire = 2       |
| REACTIVITY | 0 | Reactivity = 0 |



Health = 1  
 Fire = 2  
 Reactivity = 0

(Contd. on page 3)

**Hazard(s) not otherwise classified (HNOC):** None known

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

**Trade name: Penofin 550 VOC Redwood All heart****3 Composition/Information on Ingredients****· Non-hazardous components:**

|            |  |       |
|------------|--|-------|
| 68333-62-0 | Fatty acids, tall-oil, polymers with ethylene glycol | 11.3% |
| 8001-20-5  | Tung Oil   | 3.27% |

**· Chemical characterization: Mixtures****· Description:** Mixture of substances listed below with non-hazardous additions.**· Dangerous Components:**

|                                     |  |        |
|-------------------------------------|--|--------|
| CAS: 64742-88-7                     | Solvent naphtha (petroleum), medium aliph.<br>⚠ Flam. Liq. 3, H226; ⚠ STOT RE 1, H372; Asp. Tox. 1, H304   | 43.54% |
| CAS: 1330-20-7<br>RTECS: ZE 2100000 | Xylene, mixture of isomers<br>⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315  | 12.44% |
| CAS: 100-41-4<br>RTECS: DA 0700000  | Ethylbenzene<br>⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332  | 3.11%  |
| CAS: 55406-53-6                     | 3-Iodo-2-propynylbutylcarbamate<br>⚠ Acute Tox. 3, H331; ⚠ STOT RE 1, H372; ⚠ Eye Dam. 1, H318;<br>⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302;<br>Skin Sens. 1, H317 | .1113% |
| CAS: 96-29-7<br>RTECS: EL9275000    | 2-butanone oxime<br>⚠ Carc. 2, H351; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H312; Skin Sens. 1, H317; Flam. Liq. 4, H227  | .1%    |

**4 First-Aid Measures****· Description of first aid measures:****· General information:**

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

**· After inhalation:**

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**· After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

**· After eye contact:** Rinse opened eye for several minutes under running water.**· After swallowing:** If swallowed and symptoms occur, consult a doctor.**· Information for doctor:****· Most important symptoms and effects, both acute and delayed:** No further relevant information available.**· Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

**5 Fire-Fighting Measures****· Extinguishing media:****· Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.**· For safety reasons unsuitable extinguishing agents:** Water

(Contd. on page 4)



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

**Trade name: Penofin 550 VOC Redwood All heart**

- **Special hazards arising from the substance or mixture:**  
Combustible liquid. Vapors can travel to a source of ignition and flash back.  
Explosive mixtures may occur at temperatures at or above flashpoint.
- **Advice for firefighters:**
- **Protective equipment:**  
Mouth respiratory protective device.  
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

### 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents  
Dispose of the collected material according to regulations.
- **Reference to other sections:**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Protect from heat.
- **Conditions for safe storage, including any incompatibilities:**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in the original container.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Protect from heat and direct sunlight.
- **Specific end use(s):** No further relevant information available.

### 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with occupational exposure limits:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

(Contd. on page 5)



### Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

Trade name: Penofin 550 VOC Redwood All heart

|  |   |
|--|---|
| <b>1330-20-7 Xylene, mixture of isomers</b>      |   |
| PEL  | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm  |
| REL  | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm   |
| TLV  | Short-term value: 651 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm<br>BEI  |
| <b>100-41-4 Ethylbenzene</b>                     |   |
| PEL  | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm  |
| REL  | Short-term value: 545 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm   |
| TLV  | Long-term value: 87 mg/m <sup>3</sup> , 20 ppm<br>BEI   |
| <b>Ingredients with biological limit values:</b> |   |
| <b>1330-20-7 Xylene, mixture of isomers</b>      |   |
| BEI  | 1.5 g/g creatinine<br>urine<br>end of shift<br>Methylhippuric acids   |
| <b>100-41-4 Ethylbenzene</b>                     |   |
| BEI  | 0.7 g/g creatinine<br>urine<br>end of shift at end of workweek<br>Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)<br><br>-<br>end-exhaled air<br>not critical<br>Ethyl benzene (semi-quantitative) |

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

### Trade name: Penofin 550 VOC Redwood All heart

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Goggles recommended during refilling.

## 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Color:

Colored

· **Odor:**

Solvent / Mineral Spirits

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Not determined.

Boiling point/Boiling range:

136 °C (277 °F)

· **Flash point:**

42 °C (108 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

265 °C (509 °F)

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not self-igniting.

· **Danger of explosion:**

Product does not present an explosion hazard.

· **Explosion limits:**

Lower:

0.6 Vol %

Upper:

7.0 Vol %

· **Vapor pressure @ 20 °C (68 °F):**

6.7 hPa (5 mm Hg)

· **Density:**

Relative density:

Not determined.

Vapor density:

Not determined.

(Contd. on page 7)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

**Trade name: Penofin 550 VOC Redwood All heart**

- Evaporation rate:** Not determined.
- **Solubility in / Miscibility with:**
  - Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 59.1 %
  - VOC content:** Not Determined
- **Solids content:** 0 %
- **Other information:** No further relevant information available.

**10 Stability and Reactivity**

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological Information**

- **Information on toxicological effects:**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:****64742-88-7 Solvent naphtha (petroleum), medium aliph.**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | >6500 mg/kg (Rat) |
| Dermal     | LD50     | >3000 mg/kg (rab) |
| Inhalative | LC50/4 h | >14 mg/l (Rat)    |

**1330-20-7 Xylene, mixture of isomers**

|            |          |                     |
|------------|----------|---------------------|
| Oral       | LD50     | 4300 mg/kg (Rat)    |
| Dermal     | LD50     | 1700 mg/kg (Rabbit) |
| Inhalative | LC50/4 h | 5000 mg/l (Rat)     |

**13463-67-7 Titanium Dioxide**

|            |          |                       |
|------------|----------|-----------------------|
| Oral       | LD50     | >10000 mg/kg (Rat)    |
| Dermal     | LD50     | >10000 mg/kg (Rabbit) |
| Inhalative | LC50/4 h | >6.82 mg/l (Rat)      |

**100-41-4 Ethylbenzene**

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 3500 mg/kg (Rat)     |
| Dermal | LD50 | 15433 mg/kg (Rabbit) |

(Contd. on page 8)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

**Trade name: Penofin 550 VOC Redwood All heart**

|   |               |                      |
|---|---------------|----------------------|
| <b>112-80-1 Oleic acid, pure</b>                  |               |                      |
| Oral  | LD50          | 74000 mg/kg (Rat)    |
| <b>55406-53-6 3-Iodo-2-propynylbutylcarbamate</b> |               |                      |
| Inhalative  | LC50/96 hours | 0.067 mg/l (Trout)   |
|   | LC50/48 hrs   | 0.04 mg/l (Daphnia)  |
| <b>96-29-7 2-butanone oxime</b>                   |               |                      |
| Oral  | LD50          | 3700 mg/kg (Rat)     |
| Dermal  | LD50          | 200-2000 mg/kg (Rat) |
| Inhalative  | LC50/4 h      | 20 mg/l (Rat)        |

- **Primary irritant effect:**

- **On the skin:**

Irritant to skin and mucous membranes.  
May cause an allergic skin reaction.

- **On the eye:** No irritating effect.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful  
Irritant

- **Carcinogenic categories:**

- **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

|            |                            |    |
|------------|----------------------------|----|
| 1330-20-7  | Xylene, mixture of isomers | 3  |
| 13463-67-7 | Titanium Dioxide           | 2B |
| 100-41-4   | Ethylbenzene               | 2B |

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

**12 Ecological Information**

- **Toxicity:**

- **Aquatic toxicity:**

|   |                           |  |
|---|---------------------------|--|
| <b>1330-20-7 Xylene, mixture of isomers</b> |                           |  |
| EC50  | 72 mg/l (Green algae)     |  |
|   | 75.49 mg/l (Daphnia)      |  |
| <b>13463-67-7 Titanium Dioxide</b>          |                           |  |
| EC50  | >1000 mg/l (Water flea)   |  |
| <b>100-41-4 Ethylbenzene</b>                |                           |  |
| EC50  | 4.9 mg/l (Green algae)    |  |
|   | 1.8-2.4 mg/l (Water flea) |  |

- **Persistence and degradability:** No further relevant information available.

(Contd. on page 9)





### Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

**Trade name: Penofin 550 VOC Redwood All heart**

- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Generally not hazardous for water.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

#### 13 Disposal Considerations

- **Waste treatment methods:**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

#### 14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, IMDG, IATA** UN1263
- **UN proper shipping name:**
- **DOT** Paint
- **ADR/ADN** UN1263 Paint
- **IMDG, IATA** PAINT
- **Transport hazard class(es):**
- **DOT**

- **Class:** 3 Combustible liquids
- **Label:** 3

· **ADR/ADN**

- **Class:** 3 Combustible liquids
- **Label:** 3

· **IMDG, IATA**

- **Class:** 3 Combustible liquids



### Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

Trade name: Penofin 550 VOC Redwood All heart

- **Label:** 3
  - **Packing group:**
  - **DOT, ADR/ADN, IMDG, IATA** III Combustible Liquids
  - **Environmental hazards:** Not applicable.
  - **Special precautions for user:** Warning: Combsutible liquids
  - **Danger code (Kemler):** 30
  - **EMS Number:** F-E,S-E
  - **Stowage Category** A
  - **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
  - **Transport/Additional information:**
  - **DOT**
  - **Quantity limitations:** On passenger aircraft/rail: 60 L  
On cargo aircraft only: 220 L
  - **Remarks:** Non-Regulated Material
- 
- **ADR/ADN**
  - **Excepted quantities (EQ):** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- 
- **IMDG**
  - **Limited quantities (LQ):** 5L
  - **Excepted quantities (EQ):** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
  - **UN "Model Regulation":** UN 1263 PAINT, 3, III

#### \*15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

|  |
|--|
| · <b>Section 355 (extremely hazardous substances):</b> |
| None of the ingredients are listed.                    |

|  |
|--|
| · <b>Section 313 (Specific toxic chemical listings):</b> |
| 1330-20-7 Xylene, mixture of isomers                     |
| 100-41-4 Ethylbenzene                                    |
| 55406-53-6 3-Iodo-2-propynylbutylcarbamate               |

|  |
|--|
| · <b>TSCA (Toxic Substances Control Act):</b>      |
| All ingredients are listed or exempt from listing. |

|   |
|---|
| · <b>California Proposition 65:</b>       |
| · <b>Chemicals known to cause cancer:</b> |
| 13463-67-7 Titanium Dioxide               |
| 100-41-4 Ethylbenzene                     |

|  |
|--|
| · <b>Chemicals known to cause reproductive toxicity for females:</b> |
| None of the ingredients are listed.                                  |



### Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

**Trade name: Penofin 550 VOC Redwood All heart**

|  |
|--|
| · <b>Chemicals known to cause reproductive toxicity for males:</b> |
| None of the ingredients are listed.                                |

|   |
|---|
| · <b>Chemicals known to cause developmental toxicity:</b> |
| None of the ingredients are listed.                       |

|   |   |
|---|---|
| · <b>Carcinogenic categories:</b>               |   |
| · <b>EPA (Environmental Protection Agency):</b> |   |
| 1330-20-7 Xylene, mixture of isomers            | I |
| 100-41-4 Ethylbenzene                           | D |

|  |    |
|--|----|
| · <b>TLV (Threshold Limit Value established by ACGIH):</b> |    |
| 1330-20-7 Xylene, mixture of isomers                       | A4 |
| 13463-67-7 Titanium Dioxide                                | A4 |
| 100-41-4 Ethylbenzene                                      | A3 |

|  |
|--|
| · <b>NIOSH-Ca (National Institute for Occupational Safety and Health):</b> |
| 13463-67-7 Titanium Dioxide  |

· **GHS label elements**  
 The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS02 GHS07

· **Signal word:** Warning

· **Hazard-determining components of labeling:**

- Xylene, mixture of isomers
- Ethylbenzene
- 3-Iodo-2-propynylbutylcarbamate
- 2-butanone oxime

· **Hazard statements:**

- H226 Flammable liquid and vapor.
- H332 Harmful if inhaled.
- H315+H320 Causes skin and eye irritation.
- H317 May cause an allergic skin reaction.

· **Precautionary statements:**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

**Trade name: Penofin 550 VOC Redwood All heart**

|                |  |
|----------------|--|
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P302+P352      | IF ON SKIN: Wash with plenty of water.   |
| P303+P361+P353 | If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312           | Call a POISON CENTER/doctor if you feel unwell.  |
| P321           | Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).   |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P333+P313      | If skin irritation or rash occurs: Get medical advice/attention.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |
| P363           | Wash contaminated clothing before reuse.   |
| P370+P378      | In case of fire: Use for extinction: CO2, powder or water spray.   |
| P403+P235      | Store in a well-ventilated place. Keep cool.   |
| P501           | Dispose of contents/container in accordance with local/regional/national/international regulations.                              |

**· National regulations:**

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other Information**

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Date of preparation / last revision:** 02/15/2018

**· Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety and Health  
OSHA: Occupational Safety & Health Administration  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
BEL: Biological Exposure Limit  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3

(Contd. on page 13)



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 02/15/2018

Reviewed on 02/15/2018

### Trade name: Penofin 550 VOC Redwood All heart

Flam. Liq. 4: Flammable liquids – Category 4  
Acute Tox. 4: Acute toxicity – Category 4  
Acute Tox. 3: Acute toxicity – Category 3  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B  
Skin Sens. 1: Skin sensitisation – Category 1  
Skin Sens. 1B: Skin sensitisation – Category 1B  
Carc. 2: Carcinogenicity – Category 2  
Carc. 2: Carcinogenicity – Category 2  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· **\* Data compared to the previous version altered.**

SDS created by MSDS Authoring Services [www.msdsauthoring.com](http://www.msdsauthoring.com) +1-877-204-9106